

101342

ShieldECO CCT Anti-glare

FEATURES

- 3 years (2 years + 1 year) extended warranty
- Matt white & clear acrylic finish
- Constructed from steel & acrylic
- Fire rated to 30, 60 & 90 minutes
- Tested with insulation cover thickness 270mm
- Suitable for bathroom zone 2
- Suitable for bathroom zone 1 if used in conjunction with a 30MA RCD
- IP65

SPEC DATA

| | |
|----------------------------|-----------------------|
| Product Wattage: | 5W |
| Product Lumen: | 520 |
| Lumen/W: | 104 |
| Kelvin: | 3000/4000/6000K |
| SDCM: | 6 |
| CRI: | 80 |
| Dimmable: | Yes |
| Lifetime (Hours): | 30000 |
| Beam Angle: | 60° |
| Power Factor: | 0.9 |
| Driver Type: | Constant Current 85mA |
| Energy Rating: | E |
| Product Voltage: | 220-240V |
| Hertz: | 50/60 |
| Surge Protection (KV): | 2 |
| Operating Temp.: | -20 to 40 Degree |
| Product Weight (KG): | 0.188 |
| Cut-out (mm): | Ø80mm |
| Minimum Cavity Depth (mm): | 80mm |
| Terminal Block: | 4-way quick fit |
| Class: | 2 |

ACCESSORIES

- 101345, Dimmer module 100W universal
- 101346, Dimmer module 250W trailing edge
- 103944, EM conversion kit 8W

